

+ Product		Company	Category	Listing Country	Cert #
- SD1010		Shield Fire Safety and Security Ltd	Non-Storage Sprinklers	United Kingdom	
Class of Work 2017 - AS, Control Mode, Pendent		Approval Standard FM 2000 - Automatic Sprinklers for Fire Protection	Certification Type FM Approved		
K 5.6		K (metric) 80	Coverage Type Standard		
Type Pendent		Response SR - Standard Response	Element 5 mm		
NPT (in.) 1/2		Finish Polyester, Brass, Chrome	Temp. Rating (°F) 135, 155, 175, 200		
Temp. Rating (°C) 57, 68, 79, 93		Sprinkler Category Non Storage	Use with Vacuum System No		
Grooved Connection No					
- SD1010		Shield Fire Safety and Security Ltd	Recessed, Flush, and Concealed Sprinklers	United Kingdom	
Class of Work 2015 - AS, Ctrl Md, Rec Fl & Concl'd		Approval Standard FM 2000 - Automatic Sprinklers for Fire Protection	Certification Type FM Approved		
K 5.6		K (metric) 80	Coverage Type Standard		
Type Recessed Pendent		Response SR - Standard Response	Element 5 mm		
NPT (in.) 1/2		Finish Brass	Temp. Rating (°F) 135, 155, 175, 200		
Temp. Rating (°C) 57, 68, 79, 93		Sprinkler Category Non Storage	Use with Vacuum System No		
Grooved Connection No					

+	Product	Company	Category	Listing Country	Cert #
–	SD1030	Shield Fire Safety and Security Ltd	Non-Storage Sprinklers	United Kingdom	
Class of Work 2017 - AS, Control Mode, Pendent K 5.6 Type Pendent NPT (in.) 1/2 Temp. Rating (°C) 68, 79, 93 Grooved Connection No Approval Standard FM 2000 - Automatic Sprinklers for Fire Protection K (metric) 80 Response QR - Quick Response Finish Polyester, Chrome, Brass Sprinkler Category Non Storage Certification Type FM Approved Coverage Type Standard Element 3 mm Temp. Rating (°F) 155, 175, 200 Use with Vacuum System No					
–	SD1030	Shield Fire Safety and Security Ltd	Recessed, Flush, and Concealed Sprinklers	United Kingdom	
Class of Work 2015 - AS, Ctrl Md, Rec Fl & Concl'd K 5.6 Type Recessed Pendent NPT (in.) 1/2 Temp. Rating (°C) 68, 79, 93 Grooved Connection No Approval Standard FM 2000 - Automatic Sprinklers for Fire Protection K (metric) 80 Response QR - Quick Response Finish Polyester, Brass, Chrome Sprinkler Category Non Storage Certification Type FM Approved Coverage Type Standard Element 3 mm Temp. Rating (°F) 155, 175, 200 Use with Vacuum System No					

+	Product	Company	Category	Listing Country	Cert #
—	SD1032	Shield Fire Safety and Security Ltd	Non-Storage Sprinklers	United Kingdom	
Class of Work 2016 - AS, Control Mode, Upright K 5.6 Type Upright NPT (in.) 1/2 Temp. Rating (°C) 68, 79, 93 Grooved Connection No Approval Standard FM 2000 - Automatic Sprinklers for Fire Protection K (metric) 80 Response QR - Quick Response Finish Chrome, Brass, Polyester Sprinkler Category Non Storage Certification Type FM Approved Coverage Type Standard Element 3 mm Temp. Rating (°F) 155, 175, 200 Use with Vacuum System No					

+	Product	Company	Category	Listing Country	Cert #
-	SD1050	Shield Fire Safety and Security Ltd	Recessed, Flush, and Concealed Sprinklers	United Kingdom	
	sd1050				
	Class of Work 2015 - AS, Ctrl Md, Rec Fl & Concl'd K 5.6 Type Concealed Pendent NPT (in.) 1/2 Temp. Rating (°C) 68, 79, 93 Grooved Connection No	Approval Standard FM 2000 - Automatic Sprinklers for Fire Protection K (metric) 80 Response SR - Standard Response Finish Brass Sprinkler Category Non Storage		FM Approved Coverage Type Standard Element 5 mm Temp. Rating (°F) 155, 175, 200 Use with Vacuum System No	