

Models SDBV, SDBB

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
SDBV-G	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	175	(1205)	a, c, d
SDBV-W	Butterfly Valve, Wafer Body	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	175	(1205)	a, c, d
SDBB-T	Butterfly Valve, Threaded Ends	1, 1 1/4, 1 1/2, 2, 2 1/2	(25, 32, 40, 50, 65)	175	(1205)	a, c, d
SDBB-G	Butterfly Valve, Grooved Ends	2, 2 1/2	(50, 65)	175	(1205)	a, c, d
SDBV-G 300	Butterfly Valve, Grooved Ends	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
SDBV-W 300	Butterfly Valve, Water Body	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
SDBB-T300	Butterfly Valve, Threaded Ends	1, 1 1/4, 1 1/2, 2, 2 1/2	(33.4, 42.4, 48.3, 60.3, 73.0)	300	(2065)	a, b, c
SDBB-G300	Butterfly Valve, Grooved Ends	1, 1 1/4, 1 1/2, 2, 2 1/2	(33.4, 42.4, 48.3, 60.3, 73.0)	300	(2065)	a, b, c

- Remarks:
- a. Available with dual supervisory switches.
 - b. FM Approved for indoor and outdoor service.
 - c. FM Approved for aboveground installations only.
 - d. FM Approved for indoor service only.

Details

Category	Indicating Valves, Butterfly or Ball Type
Class of Work	1112 - Indicating Valves
Approval Standard	FM 1112 - Indicating Valves (Butterfly or Ball Type)
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Shield Fire Safety and Security Ltd
Unit 3 Endeavor Drive, Basildon, Essex, SS14
3WF, United Kingdom
<http://www.shieldglobal.com>