

## Model SD-NRS360FF-PIF

### Product Description

Resilient Seated Gate Valves with Indicator Post flanges. 4 through 12 in. NPS. Valves have a rated working pressure of 363 psi (2500 kPa). Available with the following end connections.

### Product Specification

Model No	Valve Size		End Connection
	in	(mm)	
SD-NRS360FF-PIF	4, 6, 8, 10, 12	(100, 150, 200, 250, 300)	Flange x Flange (ANSI, BS, EN, JIS)

## Details

<b>Category</b>	Gate Valves, Inside Screw
<b>Class of Work</b>	1120 - OS&Y and NRS Gate Valves
<b>Approval Standard</b>	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
<b>Certification Type</b>	FM Approved
<b>Listing Country</b>	United Kingdom

## Company

**Shield Fire Safety and Security Ltd**  
 Unit 3 Endeavor Drive, Basildon, Essex, SS14  
 3WF, United Kingdom  
<http://www.shieldglobal.com>

## Additional Info

Automatic Sprinkler Systems

---

Valves

---

Gate Valves

---

### Gate Valves, Inside Screw

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

---