

PORTABLE MONITOR

MODEL: SD-21A

DESCRIPTION

Portable Monitor is used in the place where operator is difficult to access like hazardous storage, outdoor oil tank, gas storage tank, chemical factory. Also equipped in the fire truck to deploy during fire fighting operation at the hard to access area. Monitor is light weight for easy transportation to required area. Foldable type legs can be folded by one simple touch for quick transportation.

Vertical movement is 90° (85° above and 5° below horizontal) and horizontal movement is a full, continuous 360° (hand wheel remains stationary), grease-zerk for easy lubrication.

APPLICATION

For total flooding applications, on the outdoor hydrant, fire trucks, mines, tunnels and etc.

TECHNICAL DATA

Inlet	2½" NH female swivel
Outlet	2½" NH male
Material	Aluminum alloy (ASTM 355)
Monitor Elevation	135° vertical movement Vertical movement controlled by Handwheel
Monitor Rotation	Horizontal movement 360° with positive twist locking mechanism
Net weight	20 kg approx.



Tip Size	Flow Rate @ 7 bar
20 mm	690 LPM
23 mm	900 LPM
26 mm	1130 LPM
29 mm	1400 LPM
32 mm	1770 LPM
38 mm	2490 LPM
48 mm	4000 LPM

