

Model SD-NRV350GF-D2, SD-NRV350FG-D2, SD-NRV350FF-D2, SD-NRV350GG-D2

Product Description

Model MH-XQH-350GF-A, MH-XQH-350GF-B, MH-XQH-350F, and MH-XQH-350G

Product Specification

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
SD-NRV350GF-D2	Swing Check Valve, Flanged Inlet x Grooved Outlet Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	350	(2410)	a
SD-NRV350FG-D2	Swing Check Valve, Grooved Inlet x Flanged Outlet Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	350	(2410)	a
SD-NRV350FF-D2	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	350	(2410)	a
SD-NRV350GG-D2	Swing Check Valve, Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	350	(2410)	a

Remarks:

a. Resilient Seat

Details

Category	Check Valves, Single
Class of Work	1210 - Single Check Valves
Approval Standard	FM 1210 - Swing Check Valves
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Shield Fire Safety and Security Ltd
Unit 3 Endeavor Drive, Basildon, Essex, SS14
3WF, United Kingdom
<http://www.shieldglobal.com>