

Models SD-OSY200FF-D2, SD-OSY300FF-D2, SD-OSY300AFF-D2, SD-OSY200GG-D2, SD-OSY300GG-D2, SD-OSY300AGG-D2, SD-O SD-OSY200FG-D2,

Product Description

Resilient Seated Gate Valves. 2 through 16 in. NPS. Available with the following end connections.

Product Specification

Model No	Valve Size		Rated Working Pressure		End Connection
	in	(mm)	psi	(kPa)	
SD-OSY200FF-D2	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12, 14, 16	(50, 65, 80, 100, 125, 150, 200, 250, 300, 350, 400)	200	(1375)	Flange x Flange
SD-OSY300FF-D2	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	Flange x Flange
SD-OSY300AFF-D2	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	Flange x Flange
SD-OSY200GG-D2	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1375)	Groove x Groove
SD-OSY300GG-D2	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	Groove x Groove
SD-OSY300AGG-D2	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	Groove x Groove
SD-OSY200FG-D2	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	200	(1375)	Groove x Flange
SD-OSY300GF-D2	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	Groove x Flange
SD-OSY300AGF-D2	2 1/2, 3, 4, 5, 6, 8, 10, 12	(65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	Groove x Flange

Details

Category	Gate Valves, Outside Screw and Yoke
Class of Work	1120 - OS&Y and NRS Gate Valves
Approval Standard	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
Certification Type	FM Approved
Listing Country	United Kingdom

Company

Shield Fire Safety and Security Ltd
Unit 3 Endeavor Drive, Basildon, Essex, SS14 3WF, United Kingdom
<http://www.shieldglobal.com>