

SINGLE JACKET FIRE HOSE, TYPE 2

Single jacket fire hose consists of an impermeable elastomeric lining, a synthetic fibre reinforcement and externally applied elastomeric coating to the reinforcement. Delivery hoses are non-percolating lay flat type used in fire fighting purposes. Hoses are suitable for use with couplings with the requirements of BS 336:2010 standards. Hose is intended for use at working pressure not exceeding 15 bar. Delivery hose are manufactured to comply BS 6391: 2009 Standards.

FEATURES

- BSI Kitemark Certified.
- Light weight and flexible.
- Hose belongs to Type 2 with Elastomeric lining, Synthetic fibre reinforcement and elastomeric coating on the reinforcement.
- Hose provides good protection against the absorption of liquids and resistance of the reinforcement.
- Anti rot and anti twist.
- Hose with couplings are wound by Galvanized mild steel / SS wire.

APPLICATIONS

- Industrial and rural fire brigades as well as building protection.
- For general industrial, commercial and civil engineering applications.



HOSE DATA

| | |
|-----------------|----------------|
| Hose | : Type 2 |
| Available Color | : Red, White |
| Standard Length | : 25/30 Meters |

SPECIFICATIONS

| Model Number | Diameter (Inch.) | Working Pressure (Bar/Psi) | Burst Pressure (Bar/Psi) | Standard Compliance/Approvals |
|--------------|------------------|----------------------------|--------------------------|-------------------------------|
| SD-DH2-65R | 2.5 | 15/215 | 50/725 | BS 6391: 2009/ Kitemark |
| SD-DH2-65W | | | | |

NH threaded. Storz & instantaneous coupling or other types are available upon request.