

INDUSTRIAL FIRETRUCK

MAN TGM 4X2



FOR ANY ASSISTANCE,
PLEASE CONTACT

+44 1708 377731

info@shieldglobal.com

Shield Fire, Safety & Security Ltd
Unit 3, Endeavour Drive Basildon, Essex, SS14 3WF

Notes:

SHIELD reserve the right to introduce minor changes to improve operational and performance related aspects of the vehicle and if also necessary to supply equivalent equipment/components if they should become unavailable or obsolete.

www.shieldglobal.com



01 CHASSIS

- MAN TGM 18.290
- 18,300 kg GVW, 4x2
- 290HP @ 2200 RPM, Euro 4
- Reached up to 6 passengers

02 CREW CAB

- Accommodates 4 passengers with SCBA seats

03 BODY STRUCTURE

- Poly Propylene (PP):
- High strength
- High weldability
- Excellent chemical
- Corrosion resistance

04 STORAGE COMPARTMENT

- Six (6) capacity lockers, Three (3) on LH and RH sides
- Dust and waterproof
- Light alloy roller shutter

05 WATER PUMP

- Twin pressure pump
- Automatic Priming System
- 3000 LPM @ 10 Bar, 250 LPM @ 40 Bar

06 FOAM SYSTEM

- NAFFS-AATP
- Foam ratios: 0-6%
- UL classified as per NFPA 1901

07 WATER/FOAM TANKS

- Poly Propylene (PP)
- Water 3,8700 liters
- Foam 770 liters
- Lifetime warranty

08 ROOF MONITOR

- 4800 LPM @ 5.5 TO 10 Bar
- Horizontally 340° / Vertically +90° & -45°
- Wireless remote control

09 LIGHT MAST

- 3.22m Extended height
- 24 Voltage
- Remote Control

10 ACCESSORIES/TOOLS

- Wide range of rescue and firefighting equipment/tools
- Standard tools can be provided.

